#### WPHC14



#### WHAT'S INCLUDED:

- (1) Pelican 1430 black top loader case
- (1) Pick 'N' Pluck™ 3-level foam insert
- (1) Polymer O-ring



# CASE WITH FOAM INSERT - 1430 CRUSHPROOF, BLACK

Portable case is watertight and crushproof to provide complete protection

## **KEY FEATURES**

- High-impact polycarbonate shell resists impact and is crushproof
- Features an open cell core with a solid wall design that is strong and lightweight
- 3-level foam insert to protect equipment
- Polymer O-ring provides a waterproof seal
- IP67 weather-rated case provides protection from dust, air, and water
- Automatic pressurization equalization valve equalizes pressure inside of the case
- Features: stainless steel hardware and padlock protectors for added security

 Large, comfortable fold-down handle provides easy portability



### WPHC14

# CASE WITH FOAM INSERT - 1430 CRUSHPROOF, BLACK

Protect your equipment on-the-go with the rugged and portable Pelican 1430 Crushproof Black Top Loader Case with Foam Insert.

This Pelican case features a high-impact, crushproof Polycarbonate shell with a solid wall design and foam core that is incredibly strong and lightweight. The large, comfortable fold-down handle provides easy portability.

The case features a Polymer O-ring waterproof seal that provides protection from water, dust, and air. An automatic pressurization equalization valve equalizes pressure due to atmospheric changes.

The Pelican case also features a Pick 'N' Pluck three-piece foam insert set that includes one base pad layer, one cubed polyethylene foam layer, and one convoluted top lid foam container to protect equipment.

The Pelican 1430 also features stainless steel hardware and padlock protectors for added durability and enhanced security.

### **SPECIFICATIONS**

Dimensions	116.93" x 9.61" x 13.42" (exterior) 13.56" x 5.76" x 11.70" (interior)
Certification	DEF STAN 81-41/STANAG 4280
Construction	Polycarbonate
Product Color	Black
Outdoor	Yes
Ingress Protection	IP67
Vandal-proof	Yes
Weight (lb)	6.5

