



ALI-NS2014VR
AC-VS-NS2014VR

WITNESS SERIES



IP **4.0 Megapixel**



4MP STARLIGHT 120' IR H.265+ DOME IP CAMERA

The latest video compression format improves storage and bandwidth

Key Features:

- + 4.0 MP resolution high-definition video
- + 2688 x 1520 @30fps
- + 2.8 mm lens offers 98° field of view
- + Supports H.265, H.265+, H.264+, H.264
- + Starlight Low-Light 0.008 Lux
- + Built-in microSD/SDHC/SDXC card slot, up to 128 GB
- + SD card not included Two-way audio and built-in Microphone
- + Micro SD card slot supports up to 128GB micro SD cards (sold separately)
- + Free Alibi Witness iOS/Android mobile app

With the latest H.265+ video compression format in this Alibi 4.0 Megapixel 120' IR Outdoor Dome Security, you are sure to enjoy the improved clarity, bandwidth, and capacity of your security device.

With its 1/2.8" Progressive Scan CMOS, this camera delivers 4.0 Megapixel resolution 2688 x 1520 @30fps, providing the level of detail needed for facial recognition and license plate identification.

H.265+ is the latest video compression format that offers a vast improvement in image quality and bandwidth over

older generation devices. It also allows for faster, more fluid remote viewing, along with the ability to view more channels remotely. With H.265+ compression, you can store more information using less storage space. This camera also supports H.265, H.265+, H.264+, H.264, and MJPEG. You can also dramatically reduce file sizes with this latest video compression format.

This camera's 0.008 low lux rating, thanks to its Starlight sensors, improves night-time performance. Specifically designed for surveillance in low-light environments, not only does it enhance clarity, it also offers color images for low-light applications.

In darkness, you can rely on the camera's full frame illumination technology to see clear, sharp images up to 120' in the dark. This technology delivers a wider illumination spread and offers several advantages over standard IR, such as clearer, brighter images in low light and at night, and reduces overexposure at the center of the image and eliminates hot spots.



**SECURITY
CAMERAS DIRECT**

Security Cameras Direct
877-321-2506

<http://www.securitycamerasdirect.com>



4MP STARLIGHT 120' IR H.265+ DOME IP CAMERA

ALI-NS2014VR
AC-VS-NS2014VR

The 2.8 mm fixed lens on this camera offers a 98° field of view to cover and protect a wider area. For superior around-the-clock surveillance, you can count on the camera's 120 dB true Wide Dynamic Range (WDR) that gains better images in diverse lighting conditions, as well as 3D Digital Noise Reduction (3D-DNR) and True Day/Night (ICR).

Not only will you have better video quality, you can also rely on convenient features such as email notifications, event notification, event log, and selectable frame rate.

These cameras also come with Advanced Video Analytics that help you focus and optimize your surveillance with advanced capabilities such as Line Crossing Detection Cross, Intrusion Detection, Object Removal Detection, Unattended Baggage Detection and Face Detection.

The camera also comes with flexible storage solutions. Local storage includes micro SD card, SDHC, SDXC (not included) up to 128 GB.

For convenience, you can access your video from your iOS or Android device with a Free Alibi Witness iOS/Android App, and receive power and data over existing LAN cabling through Power over Ethernet (PoE) connection, eliminating the need to install a separate power cable, which simplifies installation and lowers cabling costs.

This product conforms to ONVIF (Open Network Video Interface Forum) specifications, such as Profile S, Profile G, PSIA, CGI, and ISAPI, for IP-based security products so you can enjoy greater compatibility with more devices.

This dome security camera is designed to withstand extreme temperatures and protected from dust and rain with an IP67 enclosure that has operating temperatures at -22 °F ~ 140 °F.

What's Included:

- + (1) 4.0 MP IP IR Dome Security Camera
- + (1) Mounting template
- + (1) Mounting hardware
- + (1) Quick start guide

Compatible with:



ALI-AA1
Outdoor Pole Mount Adapter
for ALI-AB1 and ALI-AB2
Brackets



ALI-AB3
Ceiling Pendant Mount
Bracket



ALI-AA2
Outdoor Corner Mount
Adapter



ALI-AB5
Wall Mount Bracket for Dome
Cameras




ALI-AB1
Short Wall Mount Bracket



Flange Adapter
ALI-AF4



ALI-AB2
Long Wall Mount Bracket



ALI-AJ4
Round Junction Box



SPECIFICATIONS

Imager Type	Progressive Scan CMOS
Imager Size (in)	1/2.8
Color	Yes
Camera Resolution (px)	2688 × 1520 @30fps
Megapixel	4.0
Day/Night Function	True D/N w/Mechanical Cut Filter
Digital Noise Reduction (DNR)	3D DNR
Dynamic Range (dB)	120
Electronic Shutter	1/3s - 1/100,000s
Flip	Digital Horizontal/Vertical
IR Array Range (ft)	120
IR Wavelength (nm)	850
Lux (B/W)	0.0
Lux (Color)	0.008
AGC Control	Selectable
Wide Dynamic	Yes
Relative Aperture (F-stop)	F1.2
FOV (degrees)	98°
Focus	Fixed
Lens Type	Fixed
Focal Length (mm)	2.8
Ethernet Interface	RJ-45
Ethernet Ports	1
Ethernet Speed	10/100
Protocols	TCP/IP, HTTP, HTTPS, DHCP, UDP, RTP, RTSP and more
Remote Configuration	Yes
Remote Viewable	Yes
Bit Rate	32Kbps - 16Mbps
Compression Type	H.265+, H.265, H.264, H.264+
Email Notification	Yes
Event Log	Yes
Event Notification	Yes
Selectable Frame Rate	Yes
Frame Rate (fps)	60Hz: 30fps (2048 × 1536, 1920 × 1080, 1280×720)
Motion Detection	Yes
Privacy Video Block	Yes
Storage Capacity (GB)	micro SD card, SDHC, SDXC (not included) up to 128 GB
Video Analytics Capable	Yes

Video Streaming	Tri
Dimensions	4.4" x 3.2"
SD Card Included	micro SD card, SDHC, SDXC (not included) up to 128 GB
Card Reader Type	Micro SD card, SDHC, SDXC
Certification	CE, FCC, RoHS
Construction	Aluminum
Mounting Bracket Included	Yes
Operating Humidity	0% - 95% (non-condensing)
Operating Temperature (F)	-22° - 140°
Product Color	White/Black
Outdoor	Yes
Ingress Protection	IP67
Vandal-proof	IK10
Weight (lb)	1.1
PoE	802.3af
Power (w)	12 VDC ± 25%, 5 W; PoE, 7W
Volts DC	12
Mobile App	iOS & Android
Digital Outputs	1