



ALIBI®

High Definition Surveillance



Key Features:

- + 6.0 MP resolution HD video @ 20 fps
- + 3072 x 2048 resolution
- + 2.8 mm lens offers 97° field of view
- + Supports H.265+/H.265/H.264OVC/H.264/MJPEG
- + Low-Light 0.01 Lux rating

6.0 Megapixel

IP

6.0 MEGAPIXEL 120' IR H.265+ OUTDOOR BULLET IP SECURITY CAMERA

HD camera with latest video compression technology enhances clarity and storage

This Alibi 6.0 Megapixel 120' IR Outdoor Bullet Security Camera captures and stores high-definition video using the latest H.265+ compression format that provides more storage, bandwidth, and better clarity.

The camera's 1/2.9" Progressive Scan CMOS delivers 6.0 Megapixel resolution, providing you with the level of detail needed for facial recognition and license plate identification.

H.265+ video compression format offers superior image quality and bandwidth. It also fosters faster, more fluid remote viewing, along with the ability to view more channels remotely. With H.265+ compression, you can store more information with less storage space. This camera also supports H.265, H.264 OVC, H.264, and MJPEG. See a dramatic reduction in file sizes with this latest video compression format.

This camera's 0.01 low lux rating improves night-time performance. Specifically designed for surveillance in low-light environments, not only does it enhance clarity, it also offers color images for low-light applications.

In darkness, you can rely on the camera's full frame illumination technology to see clear, sharp images up to 120' in the dark. This technology delivers a wider illumination spread and offers several advantages over standard IR, such as clearer, brighter images in low light and at night, and reduces overexposure at the center of the image and eliminates hot spots.

The 2.8 mm fixed lens on this camera offers an 97° field of view, and to address diverse lighting conditions, this camera had 120 dB true Wide Dynamic Range (WDR) that helps capture better images no matter the situation. Together with 3D Digital Noise Reduction (3D-DNR) and True Day/Night (ICR), you can enjoy superior around-the-clock surveillance.

Not only will you have better video quality, you can also rely on convenient features such as email notifications, event notification, event log, and selectable frame rate.

What's Included:

- + (1) 6.0 MP IP IR Bullet Security Camera
- + (1) Mounting template
- + (1) Mounting hardware
- + (1) Quick start guide

SECURITY CAMERAS DIRECT

Security Cameras Direct

877-321-2506

<http://www.securitycamerasdirect.com>



6.0 MEGAPIXEL 120' IR H.265+ OUTDOOR BULLET IP SECURITY CAMERA

SPECIFICATIONS

Image Type	Progressive Scan CMOS
Image Size (in)	1/2.9
Color	Yes
Camera Resolution (px)	3072 x 2048
Megapixel	6.0
Day/Night Function	True D/N w/Mechanical Cut Filter
Digital Noise Reduction (DNR)	3D DNR
Digital Range (dB)	120
Flip	Digital Horizontal/Vertical
IR Array Range (ft)	120
Lux (B/W)	0.0
Lux Color	0.01
AGC Control	OSD Selectable
Wide Dynamic	Yes
Relative Aperature (F-stop)	F1.2
FOV (degrees)	97
Focus	Fixed
Lens Type	Fixed
Max FOV (degrees)	88
Focal Length (mm)	2.8
Ethernet Interface	RJ-45
Ethernet Ports	1
Ethernet Speed	10/100
Protocols	TCP/IP, HTTP, HTTPS, DHCP, UDP, RTP, RTSP, and more
Remote Configuration	Yes
Remote Viewable	Yes
Bit Rate	32 kbps - 16 Mbps
Compression Type	Supports H.265+, H.265, H.264 OVC, H.264, MJPEG
Email Notification	Yes
Event Log	Yes
Event Notification	Yes
Selectable Frame Rate	Yes
Frame Rate (fps)	5MP @ 20 fps; 2560 x 1440 @ 30 fps
Motion Detection	Yes
Privacy Video Block	Yes
SD Card Reader	Micro SD card (not included) up to 128 GB
Storage Capacity (GB)	micro SD card, SDHC, SDXC (not included) up to 128 GB
Video Analytics Capable	Yes
Video Offload	MP4
Video Streaming	Tri

Dimensions	8.5" x 4.76" x 4.65"
SD Card Included	micro SD card, SDHC, SDXC (not included) up to 128 GB
Card Reader Type	Micro SD card, SDHC, SDXC
Certification	UL & FCC
Mounting Bracket Included	Yes
Operating Humidity	0% ~ 95% (non-condensing)
Operating Temperature (F)	-22° ~ 140°
Product Color	Black
Outdoor	Yes
Ingress Protection	IP67
Weight (lb)	0.9
PoE	802.3af
Power (w)	12 VDC ± 25%, 6W; PoE, 7W
Volts DC	12
Browser Support	Internet Explorer, Safari
Mobile App	iOS & Android