ALIBI®

VIGILANT FLEX SERIES

NDAA PRODUCT TECHNICAL REQUIREMENTS

Meets federal government technical requirements

ALIBI VIGILANT FLEX SERIES 5MP HD-TVI/AHD/CVI/ CVBS FIXED BULLET SECURITY CAMERA

Features:

+ 5MP high definition
+ Video Output: AHD/ TVI: 5M@20fps/12.5fps, 4M@30fps/15fps, 2M@30fps; CVI: 4M@30fps, 2M@30fps
+ 2592 x 1944
+ 1/ 2.5" CMOS Sensor
+ 3.6mm lens
+ 80 feet Smart IR Distance
+ DWDR (Digital Wide Dynamic Range)
+ DNR (Digital Noise Reduction)
+ IP67 rating– withstands temps from 14 degrees to 140 degrees Fahrenheit
+ Meets NDAA compliance

What's Included

+ Alibi Vigilant Flex 5MP fixed bullet security camera
+ Mounting template
+ Mounting hardware
+ Quick start guide

+ **Multi-Megapixel Resolution Video** – 5MP resolution provides exceptional clarity and detail for most applications.
+ **HD-TVI/AHD/CVI/CVBS Output** – makes this camera universal, offering cross-compatibility with other DVRs and Hybrid recorders.
+ **Smart Full-Frame IR = Better Video at Night** – Advanced full-frame illumination technology helps you capture up to 80' of nighttime video footage with more contrast and clarity.
+ **Better Images** – IR anti-reflection window increases infrared transmittance, and 3D Digital Noise Reduction assists with pixel capture and produces cleaner video.
+ **IP67 weatherproof housing** – delivering long-term durability even among extreme weather conditions such as rain, snow, and ice.
+ **Easy management** – an intuitive interface and access to the free Alibi Mobile App and makes management more straightforward than ever.

1st Choice Security & Investigations
TEXLIC: C16306

1st Choice Security
512-215-4377
http://1stchoicesecurity.alibidealer.com

SPECIFICATIONS

CAMERA	
Image Sensor	1/2.5" CMOS sensor
Image Resolution	5M:2592*1944 4M:2560*1440 2M:1920*1080
TV System	PAL/NTSC
Electronic Shutter	AUTO
Scanning System	Progressive Scan

LENS	
Focus Length	3.6mm
Field of View	90°
Focus Control	Fixed
Lens Type	Fixed

NIGHT VISION	
IR Cut Filter	YES
Infrared LED	42μ x 2PCS
Infrared Distance	25M
IR Status	AGC Auto Control

CAMERA FEATURES	
Starlight	/
Day/Night	YES
OSD Menu	YES
WDR	DWDR
UTC	YES
Noise Reduction	DNR
White Balance	AUTO / MANUAL
Gain Control	AUTO

GENERAL	
Housing	Metal, IP67
Bracket	YES
Operation Temperature	-10°C ~ +60°C RH95% Max
Storage Temperature	-20°C ~ +60°C RH95% Max
Power Source	DC12V±10%, 500mA
Dimension	171(W) x 73(H) x 70(D)mm
Weight	750g

BRACKETS & ACCESSORIES

Mini Junction Box