ALIBI®

VIGILANT PERFORMANCE SERIES

ALIBI VIGILANT PERFORMANCE 4MP STARLIGHT 98 FEET IR IP TURRET CAMERA

Key Specifications:

+ 4MP resolution, 2688 x 1520 @ 25fps
+ 2.8mm @ F1.6
+ Smart IR up to 98 feet nighttime viewing
+ Starlight technology - Colour: 0.003Lux, 0 Lux with IR
+ Built-in mic
+ MicroSD, up to 256GB
+ ANR, NAS(NFS) Network Storage
+ ONVIF (Profile S, Profile G, Profile T), API
+ Up to 120dB WDR (Wide Dynamic Range)
+ IP67 protection rating
+ Meets NDAA federal government compliance requirements

The ALIBI® Vigilant Performance Series, 4MP 98 feet IR Fixed Turret Camera delivers crisp video day or night. It also offers flexible storage solutions, with a built-in micro SD slot – enabling local storage up to 256GB and includes a built-in mic for powerful audio surveillance.

+ **3D Digital Noise Reduction (DNR)** effectively filters noise to produce a crisper, clear video stream.
+ **IP67 weatherproof housing** - this turret camera delivers long-term durability even among extreme weather conditions such as rain, snow, and ice and has a wide temperature range of -22 degrees to 140 degrees Fahrenheit.

1st Choice Security & Investigations
TEXLIC: C16306

1st Choice Security
512-215-4377
http://1stchoicesecurity.alibidealer.com

SPECIFICATIONS

CAMERA

Sensor	1/3", 4.0 megapixel, progressive scan, CMOS
Adjustment angle	Pan: 0° ~ 360° Tilt: 0° ~ 80° Rotate: 0° ~ 360°
Shutter	Auto/Manual, 1 ~ 1/100000s
Minimum Illumination	Colour: 0.003Lux (F1.6, AGC ON) 0Lux with IR on
Day/Night	IR-cut filter with auto switch (ICR)
S/N	>56dB
IR Range	Up to 30m (98ft) IR range
Wavelength	850nm
IR On/Off Control	Auto/Manual
Defog	Digital Defog
WDR	120dB

LENS

Lens Type	2.8mm@F1.6	4.0mm@F1.6
Angle Of View (H)	101.1°	83.7°
Angle Of View (V)	55.3°	44.9°
Angle Of View (O)	111.1°	89.2°

DORI DISTANCE

Lens (mm)	2.8	4.0
Detect (m)	63.0	90.0
Observe (m)	25.2	36.0
Recognize (m)	12.6	18.0
Identify (m)	6.3	9.0

VIDEO

Video Compression	Ultra 265, H.265, H.264, MJPEG
H.264 code profile	Baseline profile, Main profile, High profile
Frame Rate	Main Stream: 4MP (2688*1520), Max 25fps;4MP (2560*1440), Max 25fps; 3MP (2304*1296), Max 25fps; 1080P (1920*1080), Max 30fps; Sub Stream: 720P (1280*720), Max 30fps; D1 (720*576), Max 30fps; 640*360,Max 30fps; 2CIF(704*288), Max 30fps; CIF(352*288), Max 30fps; Third Stream: D1 (720*576), Max 30fps; 640*360,Max 30fps; 2CIF(704*288), Max 30fps; CIF(352*288), Max 30fps;
Video Bit Rate	128 Kbps-16 Mbps
9:16 Corridor Mode	Supported
OSD	Up to 8 OSDs
Privacy Mask	Up to 4 areas
ROI	Up to 8 areas
Motion Detection	Up to 4 areas

IMAGE

White Balance	Auto/Outdoor/Fine Tune/Sodium Lamp/Locked/Auto2
Digital Noise Reduction	2D/3D DNR
Smart IR	Support
Flip	Normal/Vertical/Horizontal/180°/90° Clockwise/90°Anti-clockwise
Dewarping	N/A
HLC	Supported
BLC	Supported

AUDIO

Audio Compression	G.711
Suppression	Supported
Sampling Rate	8KHZ

NETWORK

Protocols	IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, PPPoE, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, 802.1x, SNMP, QoS
Compatible Integration	ONVIF (Profile S, Profile T), API
Client	Alibi Vigilant CMS Alibi Vigilant Toolbox Alibi Vigilant Mobile
Web Browser	Plug-in required live view: IE9+, Chrome 41 and below, Firefox 52 and below Plug-in free live view: Chorme 57.0+, Firefox 58.0+, Edge 16+, Safari 11+

STORAGE

Edge Storage	Micro SD, up to 256 GB
Network Storage	ANR, NAS(NFS)

INTERFACE

Network	1 RJ45 10M/100M Base-TX Ethernet
Built-in Mic	Supported

CERTIFICATIONS

Certifications	CE: EN 60950-1 UL: UL60950-1 FCC: FCC Part 15

SPECIFICATIONS

GENERAL	
Power	DC 12V±25%, PoE (IEEE 802.3af) Power consumption: Max 4.0W
Dimensions (Ø x H)	110.5 x 94.1mm (4.4" x 3.7")
Net Weight	0.42kg (0.93lb)
Material	Metal
Operating Conditions	-30°C ~ 60°C (-22°F ~ 140°F), Humidity: ≤95% RH (non-condensing)
Strorage Environment	-30°C ~ 60°C (-22°F ~ 140°F), Humidity: ≤95% RH (non-condensing)
Surge Protection	2KV
Ingress Protection	IP67
Reset Button	N/A

COMPATIBLE BRACKETS

Junction Box
Waterproof Joint

Fixed Dome Indoor Pendent
Mount

Fixed Dome
Junction Box

Fixed Dome Outdoor Wall Mount
with Junction Box

Fixed Dome Indoor/Outdoor
Pendent Mount

Fixed Dome Indoor/Outdoor
Pendent Mount

3in Electric-box Transfer Plate for
Fixed Lens Camera

3in Electric-box Transfer Plate for
Fixed Lens Camera (wide base)

Bullet & Dome Corner Mounting
Bracket

Fixed Dome
Indoor Incline Mount

Pole Mount

4-inch Fixed Dome
Indoor Wall Mount

1st Choice Security & Investigations
TEXLIC: C16306

1st Choice Security
512-215-4377
http://1stchoicesecurity.alibidealer.com

DIMENSIONS