



4.0 Megapixel

Alibi Cloud 4MP Starlight Vandal-Resistant Fixed Dome IP Camera

KEY FEATURES

- + 4MP IP Vandal-resistant Dome Camera
- + 2.8mm fixed lens
- + Starlight chipset (.05 lux) for color in low light
- + 94 degrees Field of View
- + 98 feet Smart IR range
- + Built-in micro SD slot - up to 256GB
- + Audio & Alarm i/o
- + True Wide Dynamic Range (WDR)
- + 3D Digital Noise Reduction
- + IP67 weatherproof rating
- + IK10 vandal resistant rating
- + NDA A compliant

The 4MP dome camera with Starlight technology delivers crisp video day or night. This camera comes cloud-enabled to be used as part of the Alibi Cloud VS solution.

This product has been specifically designed and manufactured to comply with the latest technical requirements specified under NDA A regulations.

This dome camera provides superior night vision infrared performance up to 100' feet. It is built with a Starlight technology chipset to use ambient lights sources to produce color video at night. The camera offers long-term durability against extreme weather conditions such as rain, snow, and ice with a wide temperature range of -40 degrees to 131 degrees Fahrenheit and features a vandal resistant housing.

Multi-megapixel resolution - Get more detail from your video camera. This camera captures high-resolution video footage that delivers crisp, precise detail and clarity for your video security needs.

Full Frame Illumination with Smart IR Smart full-frame illumination technology offers several advantages over standard IR for flawless night vision

Innovative Day/Night Scene Detection - includes a hardware sensor for smart software imaging that detects surveillance scene illumination. Designed to be water and dust-proof, this allows you to avoid unexpected costs of hardware failure.

3D Digital Noise Reduction (DNR) effectively filters noise to produce a crisper, clear video stream.

Specifications

CAMERAS

Image Sensor	1/2.8" Progressive Scan CMOS
Effective Pixels	2592(H)×1520(V)
Electronic Shutter	Auto/Manual, 1/5 - 1/20,000s
Min. illumination	Color: 0.05 Lux @ (F1.2, AGC ON) , B/W: 0 Lux @ (IR LED ON)
S/N Ratio	55dB
Day/Night	Auto(ICR)
Wide Dynamic Range	WDR
IR Range	Up to 30 m (98.4 ft)
IR On/Off Control	Auto/Manual, 1/5 - 1/20,000s
Pan/Tilt/Rotation Range	Pan: 0° - 350°, Tilt: 0° - 75°, Rotation: ±90°

LENS

Lens Type	Fixed focus
Iris Fixed	Iris
Focal Length	2.8 mm (4 mm optional)
F Number	F2.0
Angle of View	H: 93.7°, V: 53.3°

VIDEO

Max. Resolution	4MP (2592×1520)
Streaming Capability	3 Streams
Stream/Frame Rate	Stream1: 2592×1520, 2560×1440, 2304×1296, 1920×1080, 1280×720 @ 25/30fps Stream2: D1, VGA, 640×360, CIF, QVGA @ 25/30fps Stream3: VGA, CIF, QVGA @ 25/30fps
Bit Rate Control	CBR/VBR
Bit Rate	Stream1: 100kbps-16Mbps Stream2: 10kbps-6Mbps Stream3: 10kbps-3Mbps
Image Enhancement	HLC / BLC / Anti-shake / WDR
White Balance	Auto
Gain Control	Auto/Manual
Noise Reduction	2D/3D DNR
Smart IR	Support
Mirror	Support
Region of Interest	Off/On (8 Zone, Rectangle)
Motion Detection	Support
Privacy Masking	Support

Specifications

AUDIO

Compression	G.711, RAW_PCM
Bit Rate	8kbps, 16kps, 64kbps

NETWORK

Protocols	IPv4/IPv6, 802.1x, HTTP, HTTPS, TCP/IP, UDP/IP, RTSP, DHCP, NTP, RTCP/RTP, PPPoE, SMTP, DNS, UPnP, FTP, ARP, SNMP, TLS/SSL
Interoperability	ONVIF, SDK, CGI
Streaming Method	Unicast
Max. User Access	10 Users
Web Viewer	<IE11, Chrome, Firefox, Microsoft Edge
Management Software	Alibi Cloud VS


INTERFACE

Ethernet	1 Ethernet (10/100 Base-T) RJ-45 Connector
Audio	1ch Input, 1ch Output
Alarm	1ch Input, 1ch Output
Reset Button	Support
Storage	Built-in Micro SD slot, up to 256G

ELECTRICAL

Power Supply	DC12V/POE (IEEE 802.3af)
Power Consumption	Max 5.5 W
Operating Temperature	-40°C - 55°C (-40°F - 131°F)
Operating Humidity	Less than 90% RH
Ingress Protection	IP67, IK10
Certifications	CE/FCC
Casing	Metal
Dimensions	110 × 85.4mm (4.33" × 3.36")
Net Weight	0.47 kg (1.04 lb)

Dimensions



Compatible Brackets



Round Back Box
Fixed Dome



Corner Mount for All Junction
Box and Wall Mounts



Round Junction Box Dome,
Wedge Camera



Pendant Mount for
Junction Box



Pole Mount for All Junction
Box and Wall Mount



Wall Bracket with Back Box
Fixed Dome

Alibi Cloud VS is a cost-effective video surveillance solution that allows you to stream and retain video surveillance footage in an ultra-secure cloud environment. Powered by Eagle Eye Networks, a global leader in cloud video surveillance, Alibi Cloud VS is engineered to deliver cutting-edge reliability, scalability, and cyber-security.

Use the Alibi Cloud VS mobile application to view real-time videos, download footage or manage your solution. Ultra-secure, reliable and scalable - Alibi Cloud VS helps you protect your property with the latest cloud innovations.

The Alibi Cloud VS management dashboard is also available via web portal - no application needed to view and manage your camera to cloud solution on your computer or tablet.