



VIGILANT FLEX SERIES



Meets federal government technical requirements

ALIBI VIGILANT FLEX SERIES 5MP HD-TVI/AHD/CVI/CVBS FIXED BULLET SECURITY CAMERA

Features:

- + 5MP high definition
- + Video Output: AHD/TVI: 5M@20fps/12.5fps, 4M@30fps/15fps, 2M@30fps; CVI: 4M@30fps, 2M@30fps
- + 2592 x 1944
- + 1/ 2.5" CMOS Sensor
- + 3.6mm lens
- + 80 feet Smart IR Distance
- + DWDR (Digital Wide Dynamic Range)
- + DNR (Digital Noise Reduction)
- + IP67 rating- withstands temps from 14 degrees to 140 degrees Fahrenheit
- + Meets NDAA compliance
- + **Multi-Megapixel Resolution Video** - 5MP resolution provides exceptional clarity and detail for most applications.
- + **HD-TVI/AHD/CVI/CVBS Output** - makes this camera universal, offering cross-compatibility with other DVRs and Hybrid recorders.
- + **Smart Full-Frame IR = Better Video at Night** - Advanced full-frame illumination technology helps you capture up to 80' of nighttime video footage with more contrast and clarity.
- + **Better Images** - IR anti-reflection window increases infrared transmittance, and 3D Digital Noise Reduction assists with pixel capture and produces cleaner video.
- + **IP67 weatherproof housing** - delivering long-term durability even among extreme weather conditions such as rain, snow, and ice.
- + **Easy management** - an intuitive interface and access to the free Alibi Mobile App and makes management more straightforward than ever.

What's Included

- + Alibi Vigilant Flex 5MP fixed bullet security camera
- + Mounting template
- + Mounting hardware
- + Quick start guide



Alibi Security
877-711-9216
<https://alibidealer.com>

SPECIFICATIONS

CAMERA

Image Sensor	1/2.5" CMOS sensor
Image Resolution	5M:2592*1944 4M:2560*1440 2M:1920*1080
TV System	PAL/NTSC
Electronic Shutter	AUTO
Scanning System	Progressive Scan

LENS

Focus Length	3.6mm
Field of View	90°
Focus Control	Fixed
Lens Type	Fixed

NIGHT VISION

IR Cut Filter	YES
Infrared LED	42μ x 2PCS
Infrared Distance	25M
IR Status	AGC Auto Control


CAMERA FEATURES

Starlight	/
Day/Night	YES
OSD Menu	YES
WDR	DWDR
UTC	YES
Noise Reduction	DNR
White Balance	AUTO / MANUAL
Gain Control	AUTO

GENERAL

Housing	Metal, IP67
Bracket	YES
Operation Temperature	-10°C - +60°C RH95% Max
Storage Temperature	-20°C - +60°C RH95% Max
Power Source	DC12V±10%, 500mA
Dimension	171(W) x 73(H) x 70(D)mm
Weight	750g

BRACKETS & ACCESSORIES



Mini Junction Box