



VIGILANT FLEX SERIES



ALIBI VIGILANT 5 MEGAPIXEL STARLIGHT 4-IN-1HD-TVI/AHD/TVI/CVI VARIFOCAL TURRET SECURITY CAMERA

Key Specifications:

- + 5MP Resolution Dome Camera
- + 4-in-1 Video Output: HD-TVI/AHD/TVI/CVI: 5M@20fps
- + Meets NDAA Section 889 Part A Technical Requirements
- + 2.8 - 12mm varifocal lens
- + Starlight chipset captures color video in extreme low light conditions
- + 165feet extended IR range
- + DWDR (Digital Wide Dynamic Range)
- + DNR (Digital Noise Reduction)
- + IP67 rating for durability in extreme temperature conditions

The Alibi Vigilant 5 Megapixel Starlight 4-in-1 video output provides flexible installation and connectivity options. This camera produces exceptionally crisp, multi-megapixel resolution video. Easy installation and an IP67 rating to protect against extreme weather conditions make this turret camera the ideal surveillance solution for indoor or outdoor use.

The free mobile app enables you to view your live and recorded video remotely—from anywhere, from your Android or iOS mobile device.

+ What's Included:

- 5 megapixel analog fixed turret security camera
- (1) Mounting template
- (1) Mounting hardware
- Quick start guide

SPECIFICATIONS

CAMERA

Image Sensor	1 / 2.5" CMOS
Resolution	5MP
Image Size	Max. 2944 × 1656 (16:9)
Video Output	AHD / TVI / CVI / CVBS
Audio	No
Image System	PAL / NTSC
Electronic Shutter	Auto; 1/50s-1/100000s (PAL); 1/60s-1/100000(NTSC)
IR Distance	30 -50 m
Frame Rate	TVI: 2944×1656@20fps, 2560×1440@25fps/30fps AHD: 2944×1656@20fps, 2560×1440@25fps/30fps CVI:2560×1440@25fps/30fps CVBS: PAL/NTSC
Min. Illumination	Color: 0.01lux@F1.2, AGC ON; B/W: 0 lux with IR
Lens	2.8-12 mm
Lens Mount	D14
S / N Ratio	≥52dB (AGC OFF)
Ingress Protection	IP 67

FUNCTIONS

Function Control	OSD (COC Control)
Day & Night	ICR
Digital WDR	Yes
Digital NR	Yes, 2D DNR
AGC	Yes
Auto White Balance	Yes
BLC	Yes
HLC	Yes
Sharpness	Yes
Smart LED	Yes
Image Setting	Yes
Defect Correction	Auto
Language	Chinese and English
Angle Adjustment	Pan: 0°-360°; Tilt: 0°-80°; Rotation: 0°-360°

OTHERS

Power Supply	DC12V (± 15%)
Power Consumption	IR OFF : < 1W; IR ON : < 6W
Working Environment	- 30 °C - 50 °C, 10 % - 90 % (relative humidity)
Dimensions (mm)	111.5 x 99.6
Weight (net)	Approx. 0.55KG

DIMENSIONS

