ALIBI®

VIGILANT FLEX SERIES

NDAA PRODUCT TECHNICAL REQUIREMENTS

Meets federal government technical requirements

ALIBI VIGILANT FLEX SERIES 2MP HD-TVI/AHD/ CVI/CVBS FIXED TURRET SECURITY CAMERA

Features:

+ 2MP high definition
+ 1920 x 1080
+ 1/3" CMOS Sensor
+ 3.6mm lens
+ 65 feet Smart IR Distance
+ DWDR (Digital Wide Dynamic Range)
+ DNR (Digital Noise Reduction)
+ IP67 rating – withstands temps from 14 degrees to 140 degrees Fahrenheit
+ Meets NDAA compliance

What's Included

+ 2MP IP 65' IR fixed turret security camera
+ Mounting template
+ Mounting hardware
+ Quick start guide

+ **Multi-Megapixel Resolution Video** – 2MP resolution provides exceptional clarity and detail for most applications.
+ **Smart Full-Frame IR = Better Video at Night** – Advanced full-frame illumination technology helps you capture up to 65' of nighttime video footage with more contrast and clarity.
+ **Better Images** – IR anti-reflection window increases infrared transmittance, and 3D Digital Noise Reduction assists with pixel capture and produces cleaner video.
+ **HD-TVI/AHD/CVI/CVBS Output** – provides easy connectivity to any analog or HD-TVI camera on any analog channel, efficiently supporting all cameras on your network.
+ **IP67 weatherproof housing** – offers protection and long term durability among extreme weather conditions such as rain, snow, and ice.
+ **Easy management** – an intuitive interface and access to the free Alibi Mobile App and makes management more straightforward than ever.

NEWBERRY BLACKWELL ELECTRIC LLC FLORIDA

BLACKWELL ELECTRIC

Blackwell Electric
3524726104
https://www.blackwellelectric.net/

SPECIFICATIONS

CAMERA	
Image Sensor	1/3" CMOS Sensor
Image Resolution	2M:1920*1080
TV System	PAL/NTSC
Electronic Shutter	AUTO
Scanning System	Progressive Scan

LENS	
Focus Length	3.6mm
Field of View	79°
Focus Control	Fixed
Lens Type	Fixed

NIGHT VISION	
IR Cut Filter	YES
Infrared LED	14μ x 18PCS
Infrared Distance	20M
IR Status	AGC Auto Control

CAMERA FEATURES	
Starlight	/
Day/Night	YES
OSD Menu	YES
WDR	DWDR
UTC	YES
Noise Reduction	DNR
White Balance	AUTO / MANUAL
Gain Control	AUTO

GENERAL	
Housing	Metal, IP67
Bracket	NO
Operation Temperature	-10°C ~ +60°C RH95% Max
Storage Temperature	-20°C ~ +60°C RH95% Max
Power Source	DC12V±10%, 550mA
Dimension	93 (Dia) x 74(H) mm
Weight	400g

BRACKETS & ACCESSORIES

Junction Box

Wall Bracket for Varifocal Turret Cameras