



VIGILANT FLEX SERIES



Meets federal government technical requirements

ALIBI VIGILANT FLEX SERIES 2MP STARLIGHT HD-TVI/AHD/CVI/ CVBS FIXED BULLET CAMERA

Key Specifications:

- + 2MP Resolution Bullet Camera
- + SONY Starvis chipset for color in low light
- + 4-in-1 Video Output: HD-TVI/ AHD/TVI/CVI: 2M@30fps
- + 2.8mm fixed lens
- + 200 feet IR range
- + NDAA compliant
- + DWDR (Digital Wide Dynamic Range)
- + DNR (Digital Noise Reduction)
- + IP67 rating- withstands temps from 14 degrees to 140 degrees Fahrenheit

- + **Multi-megapixel resolution** - Get more detail from your video camera. This camera captures high-resolution video footage that delivers crisp, precise detail and clarity for your video security needs.
- + **Full Frame Illumination with Smart IR** - Smart full-frame illumination technology offers several advantages over standard IR for flawless night vision, including:
 - Clearer, brighter images in low light and at night
 - Reduces overexposure of the IR LEDs at the center of the image
 - Increases illuminant efficiency up to 30%
 - Produces LED light in rectangle form to better fit screen size
 - Captures images up to 65 feet in the dark without washing out the subject at closer ranges
 - Reduces video noise for a clearer nighttime picture and reduces bandwidth consumption and video storage requirements
- + **Innovative Day/Night Scene Detection** - includes a hardware sensor for smart software imaging that detects surveillance scene illumination. Designed to be water and dust-proof, this allows you to avoid unexpected costs of hardware failure.
- + **Intuitive interface** - everything you need to manage your system at your fingertips. With an intuitive interface and access to the free Alibi CMS and mobile app, system management has never been simpler.

SPECIFICATIONS

CAMERA

| | |
|--------------------|--|
| Image Sensor | 1/2.8" SONY Starvis Back-illuminated CMOS Sensor |
| Image Resolution | 2M:1920*1080 |
| TV System | PAL/NTSC |
| Electronic Shutter | AUTO / MANUAL |
| Scanning System | Progressive Scan |

LENS

| | |
|---------------|-------|
| Focus Length | 2.8mm |
| Field of View | 79° |
| Focus Control | Fixed |
| Lens Type | Fixed |

NIGHT VISION

| | |
|-------------------|------------------|
| IR Cut Filter | YES |
| Infrared LED | 42μ x 6PCS |
| Infrared Distance | 60M |
| IR Status | AGC Auto Control |

CAMERA FEATURES

| | |
|-----------------|---------------|
| Starlight | YES |
| Day/Night | YES |
| OSD Menu | YES |
| WDR | YES |
| UTC | YES |
| Noise Reduction | 3DNR |
| Coaxial Audio | / |
| White Balance | AUTO / MANUAL |
| Gain Control | AUTO |

GENERAL

| | |
|-----------------------|----------------------------|
| Housing | Metal, IP67 |
| Bracket | YES |
| Operation Temperature | -10° - +60° RH95% Max |
| Storage Temperature | -20° - +60° RH95% Max |
| Power Source | DC12V±10%, 900mA |
| Dimension | 220(W) x 105(H) x 109(D)mm |
| Weight | 2150g |

BRACKETS



Large Round Junction Box
for Varifocal Cameras