



VIGILANT FLEX SERIES



ALIBI VIGILANT FLEX SERIES 5MP HD-TVI/AHD/CVI/CVBS STARLIGHT ILLUMINITE FIXED BULLET SECURITY CAMERA

Key Specifications:

- + 5MP high definition
- + Video Output: AHD/
TVI: 8M@15fps/12.5fps,
4M@30fps/15fps, 2M@30fps; CVI:
8M@15fps
- + 1/ 2.5" CMOS Sensor
- + .03 Lux Rating
- + Starlight Chipset
- + 3.6mm lens
- + 82 feet Smart IR Distance
- + Audio over Coax
- + DWDR (Digital Wide Dynamic
Range)
- + DNR (Digital Noise Reduction)
- + IP67 rating- withstands temps
from 14 degrees to 140 degrees
Fahrenheit
- + Meets NDAA compliance

As part of the Alibi Vigilant Flex Series, this 5MP 4-in-1 Fixed Bullet Security Camera delivers crisp video day or night, providing HD-TVI/AHD/CVI/CVBS output for compatibility. Connect to other DVRs and Hybrid recorders with one easy solution.

This product has been specifically designed and manufactured to comply with the latest technical requirements specified under NDAA regulations.

Protecting your home or business has never been easier – or more convenient. The 5MP HD-TVI bullet security camera offers an impressive 82 feet IR – perfect for after-hours surveillance or anywhere you need to capture bright footage in dark conditions to protect your business. Whether it's 12pm or 12am, this versatile indoor/outdoor camera provides clear, crisp surveillance.

- + **Multi-Megapixel Resolution Video** – 5MP resolution allows you to capture a high level of clarity and detail for most applications
- + **3D Digital Noise Reduction (DNR)** effectively filters noise to produce a more crisp, clear video stream.
- + **IP67 weatherproof housing** –this camera can handle long-term durability even among extreme weather conditions such as rain, snow, and ice.
- + **IllumiNite Technology featuring Starlight chipsets** – features an HD progressive scan CMOS sensor, capturing clear and vivid color images day or night – even in extremely dark environments.

CNY SECURITY SOLUTIONS LLC

3156555894

<http://CNY.alibidealer.com>

SPECIFICATIONS

CAMERA

Image Sensor	1/2.5" CMOS sensor
Image Resolution	8M:3840*2160 5M:2592*1944 4M:2560*1440 2M:1920*1080
TV System	PAL/NTSC
Electronic Shutter	Auto
Minimum Illumination	Color : 0.03 lux@F2.0, 0 Lux with white light
Scanning System	Progressive Scan

LENS

Focus Length	3.6mm
Focus Control	Fixed
Lens Type	Fixed

NIGHT VISION

IR Cut Filter	YES
Infrared LED	NO, Support Warm white (4000K)
Light Distanc	up to 25m
IR Status	AGC auto control

CAMERA FEATURES

Starlight	N/A
Day/Night	Color
OSD Menu	YES
WDR	DWDR
UTC	YES
Noise Reduction	DNR
Coaxial Audio	YES (only TVI)
White Balance	AUTO / MANUAL
Gain Control	AUTO

GENERAL

Housing	Metal, IP67
Bracket	YES
Operation Temperature	-10°C - +60°C RH95% Max
Storage Temperature	-20°C - +60°C RH95% Max
Power Source	DC12V±10%, 450mA
Dimension	171(W) x 73(H) x 73(D)mm
Weight	750g

COMPATIBLE BRACKETS



Junction Box

DIMENSIONS

