



VIGILANT FLEX SERIES



Meets federal government technical requirements

ALIBI VIGILANT FLEX SERIES 2MP HD-TVI/AHD/CVI/ CVBS VARIFOCAL DOME CAMERA

Key Specifications:

- + 2MP Varifocal Dome Camera
- + Video Output: AHD/TVI/CVI: 2M@30fps
- + 2.8 to 12 mm manual varifocal lens
- + SONY Starvis chipset for color in low light
- + 98 feet IR range
- + DWDR (Digital Wide Dynamic Range)
- + DNR (Digital Noise Reduction)
- + Vandal-resistant housing design
- + IP67 rating - withstands temps from -22 degrees to 140 degrees Fahrenheit
- + Meets NDA A Compliance
- + **Multi-megapixel resolution** - Get more detail from your video camera. This camera captures high-resolution video footage that delivers crisp, precise detail and clarity for your video security needs.
- + **Full Frame Illumination with Smart IR** - Smart full-frame illumination technology offers several advantages over standard IR for flawless night vision.
- + **3D Digital Noise Reduction (DNR)** effectively filters noise to produce a crisper, clear video stream.
- + **IP67 weatherproof housing** - long-term durability even among extreme weather conditions such as rain, snow, and ice.
- + **Innovative Day/Night Scene Detection** - includes a hardware sensor for smart software imaging that detects surveillance scene illumination. Designed to be water and dust-proof, this allows you to avoid unexpected costs of hardware failure.
- + **Intuitive interface** - everything you need to manage your system at your fingertips. With an intuitive interface and access to the free Alibi CMS and mobile app, system management has never been simpler.



CovertWitness.com
Hi Def Security Systems

Covert Witness

951-220-0680

<http://covertwitness.alibidealer.com>

SPECIFICATIONS

CAMERA

| | |
|--------------------|------------------|
| Image Sensor | 1/3" CMOS Sensor |
| Image Resolution | 2M:1920*1080 |
| TV System | PAL/NTSC |
| Electronic Shutter | Auto |
| Scanning System | Progressive Scan |

LENS

| | |
|---------------|-----------|
| Focus Length | 2.8-12mm |
| Field of View | 94-32° |
| Focus Control | Manual |
| Lens Type | Varifocal |

NIGHT VISION

| | |
|-------------------|------------------|
| IR Cut Filter | YES |
| Infrared LED | 42μ x 4PCS |
| Infrared Distance | 30M |
| IR Status | AGC Auto Control |

CAMERA FEATURES

| | |
|-----------------|---------------|
| Starlight | / |
| Day/Night | YES/NO |
| OSD Menu | YES |
| WDR | DWDR |
| UTC | YES |
| Noise Reduction | 3DNR |
| Coaxial Audio | / |
| White Balance | AUTO / MANUAL |
| Gain Control | AUTO |

GENERAL

| | |
|-----------------------|-------------------------|
| Housing | Metal, IP67 |
| Bracket | Optional |
| Operation Temperature | -10°C - +60°C RH95% Max |
| Storage Temperature | -20°C - +60°C RH95% Max |
| Power Source | DC12V±10%, 750mA |
| Dimension | 5.51" x 4.84"(H) |
| Weight | 2.65 lbs. |

BRACKETS



Wall Bracket for Varifocal Turret Cameras

