

VIGILANT FLEX SERIES





ALIBI VIGILANT FLEX SERIES 5MP HD-TVI/AHD/CVI/CVBS FIXED BULLET SECURITY CAMERA

Features:

- + 5MP high definition
- + Video Output: AHD/
 TVI: 5M@20fps/12.5fps,
 4M@30fps/15fps, 2M@30fps;
 CVI: 4M@30fps, 2M@30fps
- + 2592 x 1944
- + 1/ 2.5" CMOS Sensor
- + 3.6mm lens
- + 80 feet Smart IR Distance
- + DWDR (Digital Wide Dynamic Range)
- + DNR (Digital Noise Reduction)
- + IP67 rating- withstands temps from 14 degrees to 140 degrees Eahrenheit
- + Meets NDAA compliance

What's Included

- + Alibi Vigilant Flex 5MP fixed bullet security camera
- + Mounting template
- + Mounting hardware
- + Quick start guide

- + Multi-Megapixel Resolution Video 5MP resolution provides exceptional clarity and detail for most applications.
- + HD-TVI/AHD/CVI/CVBS Output makes this camera universal, offering cross-compatibility with other DVRs and Hybrid recorders.
- + Smart Full-Frame IR = Better Video at Night Advanced full-frame illumination technology helps you capture up to 80' of nighttime video footage with more contrast and clarity.
- + **Better Images** IR anti-reflection window increases infrared transmittance, and 3D Digital Noise Reduction assists with pixel capture and produces cleaner video.
- + **IP67 weatherproof housing** delivering long-term durability even among extreme weather conditions such as rain, snow, and ice.
- + Easy management an intuitive interface and access to the free Alibi Mobile App and makes management more straightforward than ever.

SPECIFICATIONS

BRACKETS & ACCESSORIES

CAMERA

Image Sensor 1/2.5" CMOS sensor

Image Resolution 5M:2592*1944 4M:2560*1440

2M:1920*1080

TV System PAL/NTSC Electronic Shutter AUTO

Scanning System Progressive Scan



Mini Junction Box

LENS

Focus Length 3.6mm
Field of View 90°
Focus Control Fixed
Lens Type Fixed

NIGHT VISION

 $\begin{array}{ll} \text{IR Cut Filter} & \text{YES} \\ \\ \text{Infrared LED} & 42 \mu \, \text{x 2PCS} \\ \\ \text{Infrared Distance} & 25 \text{M} \\ \end{array}$

IR Status AGC Auto Control

CAMERA FEATURES

Starlight //
Day/Night YES
OSD Menu YES
WDR DWDR
UTC YES
Noise Reduction DNR

White Balance AUTO / MANUAL

Gain Control AUTO

GENERAL

Housing Metal, IP67
Bracket YES

 $\begin{array}{lll} \text{Operation Temperature} & -10^{\circ}\text{C} ~ +60^{\circ}\text{C} ~ \text{RH95\% Max} \\ \text{Storage Temperature} & -20^{\circ}\text{C} ~ +60^{\circ}\text{C} ~ \text{RH95\% Max} \\ \text{Power Source} & \text{DC12V\pm10\%, 500mA} \\ \text{Dimension} & 171(W) \times 73(H) \times 70(D)\text{mm} \end{array}$

Weight 750g