



VIGILANT FLEX SERIES



Meets federal government technical requirements

ALIBI VIGILANT FLEX SERIES 2MP HD-TVI/AHD/ CVI/ CVBS FIXED TURRET SECURITY CAMERA

Features:

- + 2MP high definition
- + 1920 x 1080
- + 1/3" CMOS Sensor
- + 3.6mm lens
- + 65 feet Smart IR Distance
- + DWDR (Digital Wide Dynamic Range)
- + DNR (Digital Noise Reduction)
- + IP67 rating - withstands temps from 14 degrees to 140 degrees Fahrenheit
- + Meets NDAA compliance

What's Included

- + 2MP IP 65' IR fixed turret security camera
- + Mounting template
- + Mounting hardware
- + Quick start guide

- + **Multi-Megapixel Resolution Video** - 2MP resolution provides exceptional clarity and detail for most applications.
- + **Smart Full-Frame IR = Better Video at Night** - Advanced full-frame illumination technology helps you capture up to 65' of nighttime video footage with more contrast and clarity.
- + **Better Images** - IR anti-reflection window increases infrared transmittance, and 3D Digital Noise Reduction assists with pixel capture and produces cleaner video.
- + **HD-TVI/AHD/CVI/ CVBS Output** - provides easy connectivity to any analog or HD-TVI camera on any analog channel, efficiently supporting all cameras on your network.
- + **IP67 weatherproof housing** - offers protection and long term durability among extreme weather conditions such as rain, snow, and ice.
- + **Easy management** - an intuitive interface and access to the free Alibi Mobile App and makes management more straightforward than ever.

SPECIFICATIONS

CAMERA

Image Sensor	1/3" CMOS Sensor
Image Resolution	2M:1920*1080
TV System	PAL/NTSC
Electronic Shutter	AUTO
Scanning System	Progressive Scan

LENS

Focus Length	3.6mm
Field of View	79°
Focus Control	Fixed
Lens Type	Fixed

NIGHT VISION

IR Cut Filter	YES
Infrared LED	14μ x 18PCS
Infrared Distance	20M
IR Status	AGC Auto Control

CAMERA FEATURES

Starlight	/
Day/Night	YES
OSD Menu	YES
WDR	DWDR
UTC	YES
Noise Reduction	DNR
White Balance	AUTO / MANUAL
Gain Control	AUTO

GENERAL

Housing	Metal, IP67
Bracket	NO
Operation Temperature	-10°C - +60°C RH95% Max
Storage Temperature	-20°C - +60°C RH95% Max
Power Source	DC12V±10%, 550mA
Dimension	93 (Dia) x 74(H) mm
Weight	400g

BRACKETS & ACCESSORIES



Junction Box



Wall Bracket for Varifocal Turret Cameras