



VIGILANT PERFORMANCE SERIES



Meets federal government technical requirements

ALIBI VIGILANT FLEX SERIES 2MP ILLUMINITE STARLIGHT FIXED HD-TVI/AHD/CVI/CVBS TURRET CAMERA

Key Specifications:

- + 2MP high-resolution
- + 1/2.8" CMOS sensor
- + 3.6mm fixed lens
- + 82' IR
- + IP67 weather rating

This 2MP 4-in-1 Fixed Turret Security Camera delivers crisp video day or night, providing HD-TVI/AHD/CVI/CVBS output for compatibility. Connect to any analog cameras on your network with one easy solution.

This product has been designed and manufactured to comply with the latest technical requirements specified under NDAA regulations.

The 2MP turret security camera offers 80 feet IR crisp nighttime video footage and features a 3.6mm wide-angle lens and Up the Coax (UTC) technology that enables you to control the camera onscreen display (OSD) from your web browser and the Alibi CMS or smartphone app.

- + **Multi-Megapixel Resolution Video** – 2MP resolution allows you to capture a high level of clarity and detail for most applications
- + **3D Digital Noise Reduction (DNR)** effectively filters noise to produce a crisper, clear video stream.
- + **IP67 weatherproof housing** – this camera can handle long-term durability even among extreme weather conditions such as rain, snow, and ice.
- + **Innovative Day/Night Scene Detection** – includes a hardware sensor for smart software imaging that detects surveillance scene illumination. Designed to be water and dust-proof, this allows you to avoid unexpected costs of hardware failure.
- + **Intuitive interface** – everything you need to manage your system at your fingertips. With an intuitive interface and access to the free Alibi CMS and mobile app, system management has never been simpler.



Drc Technologies
610-502-0854
www.drc-tech.net

SPECIFICATIONS

CAMERA

| | |
|--------------------|--|
| Image Sensor | 1/2.8" SONY Starvis Back-illuminated CMOS sensor |
| Image Resolution | 5M:2592*1944 4M:2560*1440 2M:1920*1080 |
| TV System | PAL/NTSC |
| Electronic Shutter | Auto |
| Scanning System | Progressive Scan |

LENS

| | |
|---------------|-------|
| Focus Length | 3.6mm |
| Field of View | 88° |
| Focus Control | Fixed |
| Lens Type | Fixed |

NIGHT VISION

| | |
|---------------|--------------------------------|
| IR Cut Filter | YES |
| Infrared LED | NO, Support Warm white (4000K) |
| Light Distanc | up to 25m |
| IR Status | AGC auto control |

CAMERA FEATURES

| | |
|-----------------|---------------|
| Starlight | YES |
| Day/Night | Color |
| OSD Menu | YES |
| WDR | YES |
| UTC | YES |
| Noise Reduction | AI-DNR |
| Coaxial Audio | / |
| White Balance | AUTO / MANUAL |
| Gain Control | AUTO |

GENERAL

| | |
|-----------------------|-----------------------|
| Housing | Metal, IP67 |
| Bracket | Optional |
| Operation Temperature | -10° - +60° RH95% Max |
| Storage Temperature | -20° - +60° RH95% Max |
| Power Source | DC12V±10%, 450mA |
| Dimension | 109 x 93(H) mm |
| Weight | 800g |

BRACKETS



Wall Bracket