



VIGILANT PERFORMANCE SERIES



ALIBI VIGILANT FLEX SERIES 4MP IP FIXED TURRET NETWORK CAMERA

Key Specifications:

- + 4MP IP turret camera
- + 2.8mm lens
- + 97.0 degrees Field of View
- + DORI Distance: Detect 63.0m, Observe 25.2m, Recognize 12.6m, Identify 6.3m
- + 98 feet Smart IR Distance
- + .02 low-light Lux Rating
- + Built-In Microphone
- + Supports Ultra H.265, H.265, H.264, MJPEG
- + DWDR (Digital Wide Dynamic Range)
- + Supports up to 128GB Micro SD-Card
- + NDAA compliant
- + IP67 rating - withstands temps from -22 degrees to 140 degrees Fahrenheit

The Alibi Vigilant Flex Series 4MP Fixed Turret Security Camera delivers crisp video day or night.

This product has been specifically designed and manufactured to comply with the latest technical requirements specified under NDAA regulations.

- + **Multi-Megapixel Resolution Video** - 4MP camera captures a high level of clarity and detail for most applications
- + **IP67 weatherproof housing** this turret camera has a wide temperature range of -22 degrees to 140 degrees Fahrenheit - delivering long-term durability even among extreme weather conditions such as rain, snow, and ice.
- + **Multi-megapixel resolution** - Get more detail from your video camera. This camera captures multi-megapixel resolution video footage that delivers crisp, precise detail and clarity for your video security needs.
- + **Innovative Day/Night Scene Detection** - includes a hardware sensor for smart software imaging that detects surveillance scene illumination. Designed to be water and dust-proof, this allows you to avoid unexpected costs of hardware failure.
- + **HTML5 Plugin Free** - use on almost any Browser for support.
- + **Ultra H.265 Compression** - reduce bandwidth and storage requirements. With Ultra H.265 compression technology, you can store more information using less hard drive space. Ultra H.265 also helps you minimize bandwidth requirements for high-resolution video and makes the remote viewing less demanding on the recorder.
- + **Intuitive interface** - everything you need to manage your system at your fingertips. With an intuitive interface, along with access to the free Vigilant Mobile App and Vigilant CMS, system management has never been simpler.

SPECIFICATIONS

CAMERA

| | |
|-------------------------|---|
| Sensor | 1/2.7", progressive scan, CMOS |
| Lens | 2.8mm@F2.1 |
| Angle of View (H) | 112.7° |
| Angle of View (V) | 60.1° |
| Angle of View (O) | 146.5° |
| Adjustment angle | Pan: 0° - 360° Tilt: 0° - 80° Rotate: 0° - 360° |
| Shutter | Auto/Manual, 1 - 1/1000000s |
| Minimum Illumination | Colour: 0.02Lux (F2.1, AGC ON) 0Lux with IR on |
| Digital noise reduction | 2D/3D DNR |
| Day/Night | IR-cut filter with auto switch (ICR) |
| S/N | >52dB |
| IR Range | Up to 30m (98ft) IR range |
| Defog | Digital Defog |
| WDR | DWDR |

DORI DISTANCE

| | | |
|---------------|------|------|
| Lens (mm) | 2.8 | 4.0 |
| Detect (m) | 56.0 | 80.0 |
| Observe (m) | 22.4 | 32.0 |
| Recognize (m) | 11.2 | 16.0 |
| Identify (m) | 5.6 | 8.0 |

VIDEO

| | |
|--------------------|--|
| Video Compression | Ultra 265, H.265, H.264, MJPEG |
| H.264 code profile | Baseline profile, Main Profile |
| Frame Rate | Main Stream: 4MP (2560*1440), Max 20fps; 1080P (1920*1080), Max 20fps; Sub Stream: 720P (1280*720), Max 20fps |
| HLC | Supported |
| BLC | Supported |
| OSD | Up to 4 OSDs |
| Privacy Mask | Up to 4 areas |
| ROI | Up to 2 areas |
| Motion Detection | Up to 4 areas |

NETWORK

| | |
|------------------------|--|
| Protocols | IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, SSL, QoS, RTMP |
| Compatible Integration | ONVIF (Profile S, Profile T), API |

INTERFACE

| | |
|---------|--------------------------|
| Network | 10/100M Base-TX Ethernet |
|---------|--------------------------|

GENERAL

| | |
|---------------------|---|
| Power | DC 12V±25%, PoE Power consumption: Max 4.5W |
| Dimensions (Ø x H) | Ø118.1 x 96.6mm (Ø4.6" x 3.8") |
| Weight | 0.27kg (0.60lb) |
| Working Environment | -30°C - 60°C (-22°F - 140°F), Humidity: ≤95% RH (non-condensing) |
| Ingress Protection | IP67 |

COMPATIBLE BRACKETS



Junction Box
Waterproof Joint



Fixed Dome Indoor Pendant
Mount



Fixed Dome and Fisheye
Junction Box



Fixed Dome Outdoor Wall Mount
with Junction Box



Fixed Dome Indoor/Outdoor
Pendent Mount



Fixed Dome Indoor/Outdoor
Pendent Mount



Pole Mount



3-inch Fixed Dome Indoor Wall
Mount

DIMENSIONS

