



VIGILANT PERFORMANCE SERIES



Meets federal government technical requirements

ALIBI VIGILANT PERFORMANCE SERIES 5MP STAINLESS STEEL STARLIGHT IP VARIFOCAL DOME CAMERA

Key Specifications:

- + 5MP IP Dome Camera
- + Stainless steel housing design - IP68 rated
- + 2.8-12mm varifocal lens
- + 65 feet Smart IR Distance
- + SONY Starvis image sensor (.001 lux) for color in low light
- + 3D Digital Noise Reduction (DNR)
- + True Wide Dynamic Range (WDR)
- + MicroSD card slot - up to 128GB
- + NDA A compliant

What's Included

- + 5MP IP varifocal dome camera
- + Mounting template
- + Mounting hardware
- + Quick start guide

Alibi Vigilant Performance Series security cameras deliver high-resolution video solutions. This camera has been specifically designed and manufactured to comply with the latest technical requirements specified under NDA A regulations.

- + **Multi-megapixel resolution** - get more detail from your video camera - 5MP camera captures crisp, high definition video at day and night. This camera captures multi-megapixel resolution video footage that delivers crisp, clear detail and clarity for your video security needs.
- + **Capture Color Video in Low Light Conditions** - SONY STARVIS chipset use ambient light sources to capture color videos in extreme low light conditions.
- + **Full Frame Illumination with Smart IR** - Smart full-frame illumination technology offers several advantages over standard IR for flawless night vision, including: Clearer, brighter images in low light and at night; Delivers a wider illumination spread; Unique rectangular IR LED design produces a uniformly illuminated image across the entire screen; Reduces overexposure at the center of the image and eliminates hot spots; Eliminates blooming from lights by reducing ambient light pollution; Reduces video noise for a clearer nighttime picture, and reduces bandwidth consumption and video storage requirements
- + **IP68 Rated for Superior Outdoor Performance** - With an IP68 weather-rated stainless steel enclosure, this camera operates in a wide range of temperatures.
- + **3D Digital Noise Reduction (DNR)** effectively filters noise to produce a more crisp, clear video stream.
- + **HTML5 Plugin Free** - use on almost any Browser for support.
- + **Ultra H.265 Compression** - reduce bandwidth and storage requirements. Capture more information using less hard drive space. Ultra H.265 also helps you minimize bandwidth requirements for high-resolution video and makes remote viewing less demanding on the recorder.
- + **Intuitive interface** - everything you need to manage your system at your fingertips. With an intuitive interface, along with access to the free Vigilant Mobile App and Vigilant CMS, system management has never been simpler.

SPECIFICATIONS

CAMERA SPECIFICATIONS

Image Sensor	1/2.8" Sony 5.69Mega STARVIS image sensor
Scan System	Progressive Scan
Total Pixels	2704(H) x 2104(V), 5.69 Mega Pixels
Effective Pixels	2616(H) x 1964(V), 5.14 Mega Pixels
Day & Night	Auto / Day(Color) / Night(BW), ICR Control
Privacy Area	On / Off (16 Programmable Zones)
Motion Detection	432 Zone, Sensitivity 1 - 5 Step, On / Off
Ext. Video	CVBS 1.0Vp-p
Real WDR	120dB
DNR	2DNR, 3DNR
Video Compression	H.265/H.264/MJPEG
Resolution	2560x1920 / 2560x1440 / 2048x1536 / 1600x1200 / 1920x1080 / 1280x1024 / 1280x960 / 640x480 / 640x36 / 320x240 / 320x180
Max. Frame Rate	Max 30fps@ all resolution
Video Quality	H.265 : Bitrate Control H.264 : Bitrate Control MJPEG : Quality Level Control
Video Streaming	Triple Stream (RTP/RTSP , Unicast RTP , Multicast RTP)
LAN Interface	RJ45 10/100-base-T Ethernet auto sensing PoE(IEEE 802.3af) Interface
Protocol	TCP/IP,UDP/IP,RTP,RTSP,RTCP,NTP, HTTP,DHCP,FTP,SMTP,DNS,DDNS
ONVIF	ONVIF Ver17.06
Power Supply	PoE, DC12[V] ± 10%
Operating Temp	32F - +122F
Humidity	0% - 90%
Lens	2.8-12mm DC auto iris motorized MP lens (ICR)
Dimension/in	4.64(W) X 3.48(H), Dome 3.14
Weight/lb	Approx. 2.88

DIMENSIONS

