



# ALIBI™

High Definition Surveillance



## 3.0 Megapixel

HD-TVI

### 3.0 MEGAPIXEL HD-TVI 65' IR OUTDOOR MINI TURRET DOME SECURITY CAMERA

Small but mighty HD-TVI camera delivers zero latency HD video over coax cable

- + 3.0 MP High-Performance CMOS, with active imaging pixel array of 2052 x 1536, produces up to 3.0 MP HD-quality video
- + 2.8mm wide angle lens provides an 84.0° FOV (Field of Vision) and covers a large area
- + Innovative Full Frame Illumination technology reduces overexposure of the IR LEDs at the center of the image, increases illumination efficiency up to 30%, produces LED light in rectangle form to better fit screen size, and captures images up to 65' in the dark without washing out the subject at closer ranges
- + An ideal 24/7 surveillance solution with features such as True Day/Night (ICR) and 120dB Wide Dynamic Range (WDR)
- + HD-TVI delivers zero latency HD video over RG59 coax or any standard analog CCTV cabling, minimizing upgrade efforts
- + Up the Coax (UTC) technology enables you to control the camera's onscreen display (OSD) from your web browser, digital video recorder interface such as the Alibi Central Management System or smart phone app
- + Measuring at a mere 3.58" x 3.25" x 2.69", its compact size provides subtle, unobtrusive surveillance
- + Temperature rating of -40° to 140°F allows camera to operate in extreme weather conditions
- + IP66 weather-rated enclosure ensures the camera is protected from particles such as dust and sand

#### What's Included:

- + 3.0 MP HD-TVI IR Outdoor Mini Turret Dome Security Camera
- + Mounting template
- + Mounting hardware
- + Quick start guide

# DRIVER TECHNOLOGY

Driver Technology

(601) 497-3450

<https://drivertechnology.alibidealer.com>



## 3.0 MEGAPIXEL HD-TVI 65' IR OUTDOOR MINI TURRET DOME SECURITY CAMERA

### SPECIFICATIONS

#### IMAGING SPECIFICATIONS

AGC Control	Built-in
Digital Noise Reduction (DNR)	Yes
S/N (dB)	62 dB
Effective Pixels (K)	2052 (H) x 1536 (V)
IR Array Range (ft)	65'
Max Analog IPS (NTSC)	18 fps
Megapixel	3.0
OSD	Yes - UTC
Wide Dynamic	Yes - WDR 120dB

#### LENS SPECIFICATIONS

Focal Length (mm)	2.8 mm
FOV (degrees)	84°

#### CONNECTORS

Video Out	HD-TVI BNC
-----------	------------

#### POWER REQUIREMENTS

Power Consumption (watts/mA)	5 Watts
Power Supply Included	No
Volts DC Input	12 Vdc

#### PHYSICAL CHARACTERISTICS

Dimensions (in)	3.58" x 3.25" x 2.69"
Relative Humidity	Humidity 90% or less (non-condensing)
Operating Temperature (F)	-40°F ~ 140°F
Product Color	White
Ingress Protection Rating	IP66
Weight (lb)	.77
Shipping Weight (lb)	1