access control accessories



Access Control Credentials

We offer a variety of access control credentials—from key fobs to access control cards. Choose from printable, durable, vertically or horizontally oriented cards, with various read ranges and numbering capabilities from some of the top brands in access control.

INFINIAS CLAMSHELL ACCESS CONTROL PROXIMITY CARD S-ACC-CLM

- Thin, durable card fits easily inside a wallet, pocket or purse
- Printable
- Consistent read range
- White card with textured surface
- Convenient card slot for attaching lanyards and badge clips

INFINIAS PVC ACCESS CONTROL PROXIMITY CARD S-ACC-PVC

- Provides convenient and secure access control at your facility
- Printable
- Consistent read range
- Glossy graphics quality surface
- Same size and thickness of a standard credit card
- Vertical or horizontal slot punch

INFINIAS ACCESS CONTROL SMART CARD

S-ACC-3020

- Features proprietary smart card technology for secure communications
- For legacy IDC smart card installations only
- Proprietary smart card technology
- 1.0" to 2.0" read range
- Printable
- CR-80 format
- 2K memory



1 help choosing? Call us today to speak with an access control technician.

Precision Security Specialist 3306070265 http://PSS.alibidealer.com

access control accessories



HID ISOPROX II ACCESS CARD WITH SPECIAL CARD NUMBERING

A-PVC-1000-SP

- Printable
- 125 kHz transmit frequency
- Sequential matching internal/external card numbering
- 2.5" to 20" read range
- Vertical or horizontal slot punch options

HID PROXCARD II ACCESS CONTROL CLAMSHELL WITH SPECIAL CARD NUMBERING A-ACC-1000-SP

- Supports up to 26 bits
- 125 kHz transmit frequency
- Offers over 137 billion unique codes
- Consistent read range
- Resistant to cracking and breaking
- Sequential matching internal/external card numbering (ink jet printed)
- White with gloss finish front
- Vertical slot punch for portrait orientation

HID ISOPROX II ACCESS CARD

A-PVC-1000

- Printable
- 125 kHz transmit frequency
- Optimized graphics quality surface for enhanced photo ID printing with direct image printers
- 2.5" to 20" read range
- Same size/thickness as standard credit card
- Vertical or horizontal slot punch options





Precision Security Specialist 3306070265 http://PSS.alibidealer.com



access control accessories



HID MULTI-TECHNOLOGY DUOPROX II ACCESS CARD

A-PVC-1100

- Printable
- Magnetic strip and proximity technology
- 125 kHz transmit frequency
- Graphics quality surface for use with direct image printers
- 2.5" to 20" read range
- Same size/thickness as standard credit card
- Vertical or horizontal slot punch options

HID PROXKEY-II WIEGAND ACCESS CONTROL KEY FOB A-AKT-1000


- RF programmable
- Supports up to 26 bits
- > 125 kHz transmit frequency
- Offers over 137 billion unique codes
- Gray with standard HID logo
- Easily fits on key ring for convenient access
- Provides universal compatibility with HID proximity readers
- External numbering provides easy identification and control

HID PROXCARD II ACCESS CONTROL CLAMSHELL

A-ACC-1000

- Supports up to 26 bits
- 125 kHz transmit frequency
- Offers over 137 billion unique codes
- Consistent read range
- Resistant to cracking and breaking
- Sequential matching internal/external card numbering (ink jet printed)
- White with gloss finish front
- Vertical slot punch for portrait orientation





Precision Security Specialist 3306070265 http://PSS.alibidealer.com



Corner 19



Access Control Credential Comparison Chart

| Product Name | infinias Clamshell Access Control Proximity Card | infinias PVC Access Control Proximity Card | infinias Access Control Smart Card* | HID ISOProx II Access Card with Special Card Numbering | HID ProxCard II Access Control Clamshell with Special Card Numbering | HID ISOProx II Access Card | HID Multi- technology DuoProx II Access Card | HID ProxKey- II Wiegand Access Control Key Fob | HID ProxCard II Access Control Clamshell |
|-----------------------------------|--|---|---|---|--|---|---|--|--|
| SKU | S-ACC-CLM | S-ACC-PVC | S-ACC-3020 | A-PVC-1000- SP | A-ACC-1000- SP | A-PVC-1000 | A-PVC-1100 | A-AKT-1000 | A-ACC-1000 |
| Read Range | 2.5" to 24" | 2.5" to 20" | 1.0" to 2.0" | 2.5" to 20" | 3.0" to 29" | 2.5" to 20" | 2.5" to 20" | 1.5" to 17.0" | 3.0" to 29" |
| Credential Type | Card | Card | Card | Card | Card | Card | Card | Key Fob | Card |
| Slot Punch | Vertical (Standard) | Horizontal or Vertical Optional | Horizontal or Vertical Optional | Horizontal or Vertical Optional | Vertical (Standard) | Horizontal or Vertical Optional | Horizontal or Vertical Optional | Key Ring Hole | Vertical (Standard) |
| Printable | Yes | Yes | Yes | Yes | No | Yes | Yes | No | No |
| Card Options | None | None | None | External card numbering (inkjet or laser engraving) Custom artwork (text or graphics) | External card numbering (inkjet only; no laser engraving) Custom artwork (text or graphics) | None | External card numbering (inkjet or laser engraving) Custom artwork (text or graphics) A variety of magnetic stripe types | None | None |
| Construc- tion | Strong, flexible and resistant to cracking and breaking | Thin, flexible polyvinyl chloride (PVC) laminate | Thin, flexible polyvinyl chloride (PVC) laminate | Thin, flexible polyvinyl chloride (PVC) laminate | Strong, flexible and resistant to cracking and breaking | Thin, flexible polyvinyl chloride (PVC) laminate | Thin, flexible polyvinyl chloride (PVC) laminate | Ultrasonically welded, ABS shell | Strong, flexible and resistant to cracking and breaking |
| Dimensions (H" x W" x D") | 2.135 x 3.385 x 0.075 | 2.125 x 3.375 x 0.033 | 2.125 x 3.375 x 0.033 | 2.125 x 3.375 x 0.033 | 2.135 x 3.385 x 0.075 | 2.125 x 3.375 x 0.033 | 2.125 x 3.375 x 0.033 | 1.90 x 0.900 x 0.550 | 2.135 x 3.385 x 0.075 |
| Operating Tempera- ture (F) | -50° ~ 160° | -50° ~ 160° | -50° ~ 160° | -50° ~ 160° | -50° ~ 160° | -50° ~ 160° | -50° ~ 160° | -50° ~ 160° | -50° ~ 160° |
| Color | White | White | White | White | White | White | White | Gray | White |
| Weight (Oz | 0.24 | 0.24 | 0.24 | 0.24 | 0.24 | 0.24 | 0.24 | 0.26 | 0.24 |
| Frequency | 125 kHz | 125 kHz | 13 mHz | 125 kHz | 125 kHz | 125 kHz | 125 kHz | 125 kHz | 125 kHz |

* Designed to run on legacy intelli-m installations only

