





ALIBI VIGILANT FLEX SERIES 2MP ILLUMINITE STARLIGHT HD-TVI/AHD/CVI/CVBS FIXED BULLET CAMERA

Key Specifications:

- + 2MP Bullet Camera
- + SONY Starvis chipset for color in low light
- + Built-in White Light LED to capture color video 24/7
- + 2.8mm fixed lens
- + NDAA compliant
- + Video Output: HD-TVI/AHD/TVI/ CVI: 2M@30fps
- + DWDR (Digital Wide Dynamic Range)
- + DNR (Digital Noise Reduction)
- + IP67 rating- withstands temps from 14 degrees to 140 degrees Fahrenheit

- + Built-in LED for Color Video 24/7/365 The powerful white light LED that is built-in just below the lens helps illuminate the field of view so you can capture color video all day and all night. The LED also can act as a deterrent during the night.
- + Multi-megapixel resolution Get more detail from your video camera. This camera captures high-resolution video footage that delivers crisp, precise detail and clarity for your video security needs.
- + Innovative Day/Night Scene Detection includes a hardware sensor for smart software imaging that detects surveillance scene illumination. Designed to be water and dust-proof, this allows you to avoid unexpected costs of hardware failure.
- + Intuitive interface everything you need to manage your system at your fingertips. With an intuitive interface and access to the free Alibi CMS and mobile app, system management has never been simpler.



SPECIFICATIONS

BRACKETS

CAMERA

Image Sensor 1/2.8" SONY Starvis Backilluminated CMOS sensor

Image Resolution 5M:2592*1944 4M:2560*1440

2M:1920*1080
TV System PAL/NTSC
Electronic Shutter Auto

Scanning System Progressive Scan



Junction Box

LENS

Focus Length 2.8mm

Field of View 107°

Focus Control Fixed

Lens Type Fixed

NIGHT VISION

IR Cut Filter YES

Infrared LED NO, Suport Warm white (4000K)

Light Distanc up to 25m

IR Status AGC Auto Control

CAMERA FEATURES

Starlight YES
Day/Night Color
OSD Menu YES
WDR YES
UTC YES
Noise Reduction AI-DNR
Coaxial Audio /

White Balance AUTO / MANUAL

Gain Control AUTO

STORAGE

Housing Metal, IP67
Bracket YES

Operation Temperature $-30^{\circ}+50^{\circ}$ RH95% Max Storage Temperature -20° ~ $+60^{\circ}$ RH95% Max Power Source DC12V±10%, 450mA Dimension 2.76'' W x 2.66'' H x 6.66'' L

(70(W) x 67.5(H) x 169(L)mm)

Weight 1.3 lbs (600g)

