ALIBI®
High Definition Surveillance

**ALI-NS2122VR**
**AC-VS-NS2122VR**

**What's Included**

+ (1) 2.0 MP IP 100′ IR Varifocal Outdoor Dome Security Camera
+ (1) Mounting template
+ (1) Mounting hardware
+ (1) Quick start guide




IP **2.0 Megapixel**

CLOUD-ENABLED

# 2.0 MEGAPIXEL WDR 100′ IR VARIFOCAL IP VANDALPROOF DOME SECURITY CAMERA

## IK10-rated impact resistant enclosure protects camera from vandalism

This Alibi 2.0 Megapixel IP dome security camera offers 100′ IR range for crisp, detailed 1920 × 1080 resolution video as it is equipped with a 2.0 MP High-Performance 1/2.8″ Progressive Scan CMOS.

As a 24/7 surveillance solution, this camera features 100′ IR range, 3D Digital Noise Reduction and 120dB Wide Dynamic Range (WDR).

This camera's 0.005 low lux rating, thanks to its Starlight sensors, improves night-time performance. Specifically designed for surveillance in low-light environments, not only does it enhance clarity, it also offers color images for low-light applications.

Cover a large area with 2.8 - 12mm motorized zoom lens that provides an 105° to 35° FOV (Field of Vision). Up the Coax (UTC) technology enables you to control the camera's onscreen display (OSD) from your web browser, digital video recorder interface such as the Alibi Central Management System or smart phone app.

This camera has smart feature analytics which include:

+ Behavior Analysis: Line crossing detection, Intrusion detection, Unattended baggage detection, Object removal detection
+ Line Crossing Detection: Enter and loiter in a pre-defined virtual region
+ Intrusion Detection: Objects left over in the pre-defined region such as the baggage, purse, dangerous materials.
+ Unattended Baggage: Objects removed from the pre-defined region, such as the exhibits on display.
+ Exception Detections: Scene change detection
+ Recognition: Face detection

The camera has a temperature rating of -22° to 140°F, and for protection from other outdoor elements such as dust and sand, the camera housing is IP67 weather-rated. In addition, the camera is vandalproof due to its IK10-rated impact resistant enclosure.

**Key Features:**

+ 2.0 Megapixel 1/2.8″ Progressive Scan CMOS
+ 1920 × 1080 resolution
+ 2.8 - 12mm motorized varifocal lens; 105° to 35° FOV
+ 120dB true WDR, 3D DNR
+ Starlight Low-Light 0.005 Lux
+ Supports H.265, H.265+, H.264+, H.264
+ -22°F -140°F
+ IP67, IK10 vandalproof
+ Built-in micro SD/ SDHC/SDXC card slot (up to 128GB)
+ 12 Vdc ±25%, PoE (802.af Class3)

SURVEILLANCE Solutions

**Surveillance Solutions**
210-898-0003
http://www.survsolutions.com

# 2.0 MEGAPIXEL WDR 100' IR VARIFOCAL IP VANDALPROOF DOME SECURITY CAMERA

**ALI-NS2122VR**
**AC-VS-NS2122VR**

## SPECIFICATIONS

| | |
|---|---|
| Image Type | Progressive Scan CMOS |
| Image Size (in) | 1/2.8 |
| Color | Yes |
| Camera Resolution (px) | 1920 x 1080 |
| Megapixel | 2.0 |
| Day/Night Function | True D/N w/Mechanical Cut Filter |
| Digital Noise Reduction (DNR) | 3D DNR |
| Digital Range (dB) | 120 |
| Electronic Shutter | 1/3s ~ 1/100,000s |
| IR Array Range (ft) | 100 |
| Lux (B/W) | 0.0 (IR ON) |
| Lux Color | 0.005 |
| AGC Control | Yes |
| Wide Dynamic | Yes |
| Relative Aperature (F-stop) | F1.2 |
| FOV (degrees) | 105° ~ 35° (Wide ~ Tele) |
| Focus | Auto |
| IR Corrective | Yes |
| Lens Type | Motorized Varifocal |
| Focal Length (mm) | 2.8 - 12 |
| Audio | Yes |
| Audio Compression | G.711/G.722.1/G.726/MP2L2 |
| Ethernet | Yes |
| Ethernet Interface | RJ45 |
| Bit Rate | 32 Kbps ~ 16 Mbps |
| Compression Type | H.265+, H.265, H.264, H.264+ |
| Frame Rate (fps) | 8MP 20 fps (3840 × 2160), 30 fps (2560 × 1920, 2560 × 1440, 1920 × 1080, 1280 × 720 |
| Motion Detection | Yes |
| Pre/Post Alarm Recording | Yes |
| Privacy Block Video | Yes |
| SD Card Reader | Micro SD card (not included) up to 128 GB |
| Dimensions | 6" Dia. x 5.2" |
| Pan Angle | 0° ~ 355° |
| Tilt Angle | 0° ~ 75° |
| Card Reader Type | SD / SDHC / SDXC card slot, up to 128gb |
| Construstion | Metal |
| Operating Humidity | 0% ~ 95% (non-condensing) |
| Operating Temperature (F) | -22° ~ 140° |

| | |
|---|---|
| Product Color | White |
| Outdoor | Yes |
| Ingress Protection | IP67 |
| Vandal-Proof | IK10 |
| Weight (lb) | 2.8 |
| Power (w) | 12 VDC ± 25% Max 9.5w, PoE (802.3af) Max 11w |
| Browser Support | Internet Explorer 8 or higher |
| Mobile App | iOS & Android |
| Sensor Inputs | 1 |
| Alarm Output | Yes |
| Alarm Outputs | 1 |
| Outputs | (1) Vp-p composite output (75Ω/BNC) |

### Compatible with:



**ALI-AA1**
**Outdoor Pole Mount Adapter for ALI-AB1 and ALI-AB2 Brackets**



**ALI-AB2**
**Long Wall Mount Bracket**



**ALI-AA2**
**Outdoor Corner Mount Adapter**



**ALI-AB3**
**Ceiling Pendant Mount Bracket**



**ALI-AB1**
**Short Wall Mount Bracket**



**ALI-AF12**
**Flange for Turret Cameras**


SURVEILLANCE Solutions

**Surveillance Solutions**
210-898-0003
http://www.survsolutions.com