



HD **2.0 Megapixel**



2.0 MEGAPIXEL STARLIGHT 130' IR WHITE LIGHT 4 IN 1 BULLET CAMERA

2 megapixel resolution with IllumiNite white light LED technology and Starlight 2.0 chipset for clear, bright images in any lighting conditions

ALI-TP3002LE is a 4 in 1 (HD-TVI/AHD/HD-CVI/CVBS) bullet camera with 2 megapixel resolution that features cutting edge technologies to help you capture hi-res, full color video 24/7/365. IllumiNite technology features a white light LED strategically placed below the camera lens that can be set to turn on at a specific time to let you capture color video any time of the night. Combined with the next gen Starlight 2.0 chipset, you have a powerful camera that lets you capture color video all night long – even in the darkest environments.

What's Included:

- + Mounting Template
- + Mounting Hardware
- + Quick Start Guide

- + **High Resolution Video** – 2 megapixel camera captures smooth video with a high level of clarity and detail
- + **IllumiNite White Light LED** – Powerful white light illuminates the surveillance area to act as a deterrent and to provide enough light to capture full color video, even in the darkest conditions
- + **Starlight 2.0 Chipset** – Super low light LUX rating means this camera can capture color video in extreme low light conditions, even without the LED.
- + **Compatibility with Existing Camera Systems** – 4 in 1 video output (switchable TVI/AHD/CVI/CVBS) offers extreme flexibility when upgrading your analog camera system
- + **Superior Outdoor Performance** – With an IP67 weather-rated metal enclosure, this bullet camera has an operating temperature rating of -40° to 140°F and is protected from elements such as dust, sand and rain



SPECIFICATIONS

Imager Type	CMOS
Color	Yes
Camera Resolution (px)	1920 (H) × 1080 (V)
Megapixel	2.0
Day/Night Function	Yes
Digital Noise Reduction (DNR)	3D DNR
Dynamic Range (dB)	130
Electronic Shutter	1/30 - 1/50,000 sec
LED Illumination Range	130
Lux (Color)	0.0005 (0.0 with light)
Wide Dynamic	Yes
FOV (degrees)	83.6°
Focus	Fixed
Focal Length (mm)	3.6
Motion Detection	Yes
Privacy Video Block	Yes
Dimensions	7.14" × 2.75" × 2.68"
Pan Angle	0°-360°
Tilt Angle	0° - 180°
Rotate Angle	0°-360°
Construction	Plastic and Metal Alloy
Operating Humidity	0% - 90% (non-condensing)
Operating Temperature (F)	-40° - 140°
Product Color	White
Outdoor	Yes
Ingress Protection	IP67
Weight (lb)	0.88
Power (w)	12 VDC ±25% Max: 3 W
Outputs	1 HD Analog; switch TVI/AHD/ CVI/CVBS

COMPATIBLE WITH:



**ALI-AJ1
Round Junction Box**



**ALI-AJ6
Mini Junction Box**