





5.0 Megapixel



## 5.0 MEGAPIXEL STARLIGHT 130' IR WHITE LIGHT 4 IN 1 BULLET

5 megapixel resolution with IllumiNite white light LED technology and Starlight 2.0 chipset for clear, bright images in any lighting conditions

ALI-TP3005L is a 4 in 1 (HD-TVI/AHD/HD-CVI/CVBS) bullet camera with 5 megapixel resolution that features cutting edge technologies to help you capture hi-res, full color video 24/7/365. IllumiNite technology features a white light LED strategically placed below the camera lens that can be set to turn on at a specific time to let you capture color video any time of the night. Combined with the next gen Starlight 2.0 chipset, you have a powerful camera that lets you capture color video all night long - even in the darkest environments.

- + High Resolution Video 5 megapixel camera captures smooth video with a high level of clarity and detail
- + IllumiNite White Light LED Powerful white light illuminates the surveillance area to act as a deterrent and to provide enough light to capture full color video, even in the darkest conditions
- + Starlight 2.0 Chipset Super low light LUX rating means this camera can capture color video in extreme low light conditions, even without the LED.
- + Compatibility with Existing Camera Systems 4 in 1 video output (switchable TVI/AHD/ CVI/CVBS) offers extreme flexibility when upgrading your analog camera system
- + Superior Outdoor Performance With an IP67 weather-rated metal enclosure, this bullet camera has an operating temperature rating of -40° to 140°F and is protected from elements such as dust, sand and rain





## **SPECIFICATIONS**

Imager Type Color	CMOS Yes
Common Developing (co.)	
Camera Resolution (px)	2560 (H) × 1944 (V)
Megapixel	5.0
Day/Night Function	Yes
Digital Noise Reduction (DNR)	3D DNR
Dynamic Range (dB)	130
Electronic Shutter	1/30 ~ 1/50,000 sec
LED Illumination Range	65
Lux (Color)	0.0005 (0.0 with light)
Wide Dynamic	Yes
FOV (degrees)	99°
Focus	Fixed
Focal Length (mm)	2.8
Motion Detection	Yes
Privacy Video Block	Yes
Dimensions	2.68" × 2.76" × 6.62"
Pan Angle	0°~360°
Tilt Angle	0° ~ 90°
Rotate Angle	0°~360°
Construction	Metal
Operating Humidity	0% ~ 90% (non-condensing)
Operating Temperature (F)	-40° ~ 140°
Product Color	White
Outdoor	Yes
Ingress Protection	IP67
Weight (lb)	0.77
Power (w)	12 VDC ±25% Max: 3.5 W
Outputs	1 HD Analog; switch TVI/AHD/ CVI/CVBS

## **COMPATIBLE WITH:**



ALI-AA1 Outdoor Pole Mount Adapter for ALI-AB1 and ALI-AB2 Brackets



ALI-AA2 Outdoor Corner Mount Adapter



ALI-AJ1 Round Junction Box



ALI-AJ4 Round Junction Box