



VIGILANT FLEX SERIES



Meets federal government technical requirements

ALIBI VIGILANT FLEX SERIES 8MP WHITE LIGHT HD-TVI/AHD/CVI/ CVBS TURRET CAMERA

Key Specifications:

- + 5MP HD-TVI/AHD/CVI/ CVBS Turret Camera
- + 3.6mm lens
- + Video Output: AHD/ TVI: 5M@20fps/12.5fps, 4M@30fps/25fps, 2M@30fps/25fps; CVI: 4M@30fps, 2M@30fps/25fps
- + White LED up to 80 feet range - 4000K rating
- + Built-in mic
- + DNR (Digital Noise Reduction)
- + IP67 rating - withstands temps from -22 degrees to 140 degrees Fahrenheit
- + Meets NDAA Compliance

- + **Multi-megapixel resolution** - Get more detail from your video camera. This camera captures high-resolution video footage that delivers crisp, precise detail and clarity for your video security needs.
- + **IllumiNite Low Light Technology** - Capture color video 24/7. IllumiNite cameras feature advanced lenses with F1.0 aperture and high performance sensors that collect and utilize more light to produce brighter images. In zero-light scenarios, built-in environmentally-friendly supplemental lighting works to guarantee colorful images.
- + **Innovative Day/Night Scene Detection** - includes a hardware sensor for smart software imaging that detects surveillance scene illumination. Designed to be water and dust-proof, this allows you to avoid unexpected costs of hardware failure.
- + **Intuitive interface** - everything you need to manage your system at your fingertips. With an intuitive interface and access to the free Alibi CMS and mobile app, system management has never been simpler.

SPECIFICATIONS

CAMERA

Image Sensor	1/2.5" CMOS sensor
Image Resolution	8M:3840*2160 5M:2592*1944 4M:2560*1440 2M:1920*1080
TV System	PAL/NTSC
Electronic Shutter	AUTO
Scanning System	Progressive Scan

LENS

Focus Length	3.6mm
Field of View	90°
Focus Control	Fixed
Lens Type	Fixed

NIGHT VISION

IR Cut Filter	YES
Infrared LED	NO, Support Warm white (4000K)
Light Distance	up to 25m
IR Status	AGC Auto Control

CAMERA FEATURES

Starlight	/
Day/Night	Color
OSD Menu	YES
WDR	/
UTC	YES
Noise Reduction	3DNR
White Balance	AUTO / MANUAL
Gain Control	AUTO
Audio	Built-in Mic

GENERAL

Housing	Metal, IP67
Bracket	Optional
Operation Temperature	-10 ~ +60 degrees RH95% Max
Storage Temperature	-20 ~ +60 degrees RH95% Max
Power Source	DC12V±10%, 450mA
Dimension	109 x 93(H) mm
Weight	600g

BRACKETS



Large Round Junction Box
for Varifocal Cameras



Wall Bracket