

VIGILANT FLEX SERIES





Powered by MStar™ chipsets that meet federal government technical requirements

2MP HD-TVI/AHD/CVI/CVBS 100' IR VARIFOCAL TURRET SECURITY CAMERA

A highly diverse varifocal lens camera offering 4-in-1 output provides extreme compatibility for all analog cameras on your network. Offering high-resolution and IP67 weather encasing, this turret camera is ideal for around-the-clock indoor and outdoor surveillance

Key Features:

- + 2MP @ 30fps
- + 1920 x 1080
- + 1/3" CMOS Sensor
- + 2.8-12mm manual zoom lens
- + 100' IR range
- + DWDR (Digital Wide Dynamic Range)
- + DNR (Digital Noise Reduction)
- + NDAA compliant

- + Multi-Megapixel Resolution Video 2MP resolution provides exceptional clarity and detail for most applications.
- + HD-TVI/AHD/CVI/CVBS Output provides easy connectivity to any analog or HD-TVI camera on any analog channel, efficiently supporting all cameras on your network.
- + Smart Full-Frame IR = Better Video at Night Advanced full-frame illumination technology helps you capture up to 100' of nighttime video footage with more contrast and clarity.
- + **Better Images** IR anti-reflection window increases infrared transmittance, and 3D Digital Noise Reduction assists with pixel capture and produces cleaner video.
- + **IP67 weatherproof housing -** delivering long-term durability even among extreme weather conditions such as rain, snow, and ice.
- + **Easy management -** an intuitive interface and access to the free Alibi Mobile App and makes management more straightforward than ever.





SPECIFICATIONS

BRACKETS & ACCESSORIES

CAMERA

 Image Sensor
 1/3" CMOS Sensor

 Image Resolution
 2M:1920*1080

 TV System
 PAL/NTSC

 Electronic Shutter
 AUTO

Scanning System Progressive Scan

LENS

Focus Length 2.8-12mm

Focus Control Manual

Lens Type Varifocal

NIGHT VISION

 $\begin{array}{lll} \text{IR Cut Filter} & \text{YES} \\ \text{Infrared LED} & 14 \mu \times 18 \text{PCS} \\ \text{Infrared Distance} & 30 \text{M} \\ \end{array}$

IR Status AGC Auto Control

CAMERA FEATURES

Starlight /
Day/Night YES
OSD Menu YES
WDR DWDR
UTC YES
Noise Reduction DNR

White Balance AUTO / MANUAL

Gain Control AUTO

GENERAL

Housing Metal, IP67

Operation Temperature -10° - +60° RH95% Max

Storage Temperature -20° - +60° RH95% Max

Power Source DC12V±10%, 750mA

Dimension 119 (Dia) x 98 (H) mm

Weight 800g



ALI-AJ1



WB02

