

VIGILANT FLEX SERIES



Powered by MStar™ chipsets
that meet federal government
technical requirements

2MP HD-TVI/AHD/CVI/CVBS 100' IR VARIFOCAL TURRET SECURITY CAMERA

A highly diverse varifocal lens camera offering 4-in-1 output provides extreme compatibility for all analog cameras on your network. Offering high-resolution and IP67 weather encasing, this turret camera is ideal for around-the-clock indoor and outdoor surveillance

Key Features:

- + 2MP @ 30fps
- + 1920 x 1080
- + 1/3" CMOS Sensor
- + 2.8-12mm manual zoom lens
- + 100' IR range
- + DWDR (Digital Wide Dynamic Range)
- + DNR (Digital Noise Reduction)
- + NDAA compliant

- + **Multi-Megapixel Resolution Video** - 2MP resolution provides exceptional clarity and detail for most applications.
- + **HD-TVI/AHD/CVI/CVBS Output** - provides easy connectivity to any analog or HD-TVI camera on any analog channel, efficiently supporting all cameras on your network.
- + **Smart Full-Frame IR = Better Video at Night** - Advanced full-frame illumination technology helps you capture up to 100' of nighttime video footage with more contrast and clarity.
- + **Better Images** - IR anti-reflection window increases infrared transmittance, and 3D Digital Noise Reduction assists with pixel capture and produces cleaner video.
- + **IP67 weatherproof housing** - delivering long-term durability even among extreme weather conditions such as rain, snow, and ice.
- + **Easy management** - an intuitive interface and access to the free Alibi Mobile App and makes management more straightforward than ever.

SPECIFICATIONS

CAMERA

Image Sensor	1/3" CMOS Sensor
Image Resolution	2M:1920*1080
TV System	PAL/NTSC
Electronic Shutter	AUTO
Scanning System	Progressive Scan

LENS

Focus Length	2.8-12mm
Focus Control	Manual
Lens Type	Varifocal

NIGHT VISION

IR Cut Filter	YES
Infrared LED	14μ x 18PCS
Infrared Distance	30M
IR Status	AGC Auto Control

CAMERA FEATURES

Starlight	/
Day/Night	YES
OSD Menu	YES
WDR	DWDR
UTC	YES
Noise Reduction	DNR
White Balance	AUTO / MANUAL
Gain Control	AUTO

GENERAL

Housing	Metal, IP67
Operation Temperature	-10° - +60° RH95% Max
Storage Temperature	-20° - +60° RH95% Max
Power Source	DC12V±10%, 750mA
Dimension	119 (Dia) x 98 (H) mm
Weight	800g

BRACKETS & ACCESSORIES



ALI-AJ1



WB02