

**VIGILANT FLEX SERIES**


Powered by MStar™ chipsets  
that meet federal government  
technical requirements

## ALIBI VIGILANT FLEX 8MP STARLIGHT 80' HD-TVI/ AHD/CVI/CVBS BULLET SECURITY CAMERA

A highly diverse camera offering 4-in-1 output provides extreme compatibility with other DVR's and Hybrid recorders. Offering ultra-high-resolution at 8MP, starlight technology and IP67 weather encasing, this bullet camera is ideal for around-the-clock indoor and outdoor surveillance

### Key Features:

- + 8MP high definition
- + Video Output: AHD: 8M@15fps, 5M@20fps; CVI: 8M@15fps, TVI: 8M@15fps, 5M@20fps
- + 1/2.8" SONY Starvis Back-illuminated CMOS sensor
- + 3.6mm lens
- + 80' range
- + TRUE WDR (Wide Dynamic Range)
- + DNR (Digital Noise Reduction)
- + Meets NDAA Compliance
- + **Multi-Megapixel Resolution Video** – 8MP resolution provides exceptional clarity and detail for most applications.
- + **Starlight Chipset** – Featuring a SONY Starvis Back-illuminated sensor, the Starlight chipset can capture excellent color images in an extremely dark environment.
- + **HD-TVI/AHD/CVI/CVBS Output** – provides extreme compatibility with other DVR's and Hybrid recorders.
- + **IP67 weatherproof housing** – delivering long-term durability even among extreme weather conditions such as rain, snow, and ice.
- + **Easy management** – an intuitive interface and access to the free Alibi Mobile App and makes management more straightforward than ever.

## SPECIFICATIONS

### CAMERA

Image Sensor	1/2.8" SONY Starvis Back-illuminated CMOS sensor
Image Resolution	8M:3840*2160 5M:2592*1944 4M:2560*1440 2M:1920*1080
TV System	PAL/NTSC
Electronic Shutter	AUTO / MANUAL
Scanning System	Progressive Scan

### LENS

Focus Length	3.6mm
Focus Control	Fixed
Lens Type	Fixed

### NIGHT VISION

IR Cut Filter	YES
Infrared LED	42μ x 2PCS
Infrared Distance	25M
IR Status	AGC Auto Control

### CAMERA FEATURES

Starlight	/
Day/Night	YES
OSD Menu	YES
WDR	YES
UTC	YES
Noise Reduction	3DNR
White Balance	AUTO / MANUAL
Gain Control	AUTO

### GENERAL

Housing	Metal, IP67
Operation Temperature	-10° ~ +60° RH95% Max
Storage Temperature	-20° ~ +60° RH95% Max
Power Source	DC12V±10%, 500mA
Dimension	171(W) x 73(H) x 70(D)mm
Weight	750g

## BRACKETS & ACCESSORIES



ALI-AJ6